## $\mathbf{A1}$

During your introductory physics classes you learned about Pascal's law, which states that in a resting fluid the pressure is isotropic, i.e. the pressing force on a test surface does not depend on the direction of the surface.

This law can be reformulated after the introduction of the stress tensor. We know that in a resting fluid there are no shearing stresses, because the shearing stress is proportional to the derivates of the velocity field: in rest the velocity is zero leading to zero shearing stress.

Pascal's reformulated law thus states: if in a medium there are no shearing stresses then the stress tensor is proport ional to the unit matrix. In this problem you have to prove this theorem, using an indirect proof.

First assume that the stress tensor is diagonal (there are no shearing stresses), but the diagonal elements are not equal:

$$\sigma = \begin{pmatrix} \sigma_{xx} & 0 & 0\\ 0 & \sigma_{yy} & 0\\ 0 & 0 & \sigma_{zz} \end{pmatrix}$$
(1)

For example let's suppose that  $\sigma_{xx} \neq \sigma_{yy}$ .

- (a) Write down the matrix that rotates the coordinate system around the z axis by an angle of  $\alpha$ .
- (b) Determine the elements of the stress tensor in this rotated coordinate system.
- (c) Express the shearing stress  $\sigma_{xy}$  in this rotated coordinate system.
- (d) Show that the shearing stress is zero for all angles only if  $\sigma_{xx} = \sigma_{yy}$ , implying that our initial assumption was wrong.

## A2

A light, elastic medium is put in a rigid box, see picture below. The bottom of the box is a square with side a, while the height of the box is b. The medium does not stick to the walls of the box, but it fills it like a jelly. The Lamé parameters of the medium are  $\lambda$  and  $\mu$ .

We start to push the surface of the medium with an unknown force F, that leads to a compression  $\Delta b$  of the surface.

- (a) Express the deformation tensor of the medium.
- (b) Write down Hooke's law for the medium.
- (c) Express the nonzero elements ( $\sigma_{xx}, \sigma_{yy}$  and  $\sigma_{zz}$ ) of the stress tensor.
- (d) Knowing the compression  $\Delta b$  determine the unknown force F.



## B1

A rod of length L, cross-section A and mass density  $\rho$  is softly fixed to the ceiling. Due to its own weight the rod elongates. In the first part of the problem you must consider this "self-elongation". The Lamé-parameters of the rod are  $\lambda$  and  $\mu$ .

Let the origin be on the ceiling and let the z axis point vertically down.

- (a) Write down the only nonzero element  $\sigma_{zz}$  of the stress tensor as a function of z.
- (b) Using Hooke's law express the nonzero elements  $\varepsilon_{xx}$ ,  $\varepsilon_{yy}$  and  $\varepsilon_{zz}$  of the deformation tensor, as a function of z.
- (c) Knowing  $\varepsilon_{zz}$ , determine the displacement  $s_z$  of the rods points as a function of z.
- (d) What is the rods  $\Delta L$  elongation?
- (e) We start to pull down the end of the rod by a force of F. Repeat the previous computations in this case too!