Artificial intelligence in data science

Backpropagation

Janos Török

Department of Theoretical Physics

October 10, 2019

Fully connected neural networks

- Ideas from Piotr Skalski (practice), Pataki Bálint Ármin (lecture) and HMKCode (lecture)



Fully connected neural networks

- Model:
  - Inputs (x_j) or for hidden layer l: A_j^{l-1}
  - Weight w_{ij}^l
  - Bias b_i^l
  - Weighted sum of input and bias: $z_i^l = \sum_j A_j^{l-1} w_{ij}^l + b_i^l$
  - Activation function (nonlinear) g: $A_i^l = g(z_i^l)$



Yang et el, 2000.

Feed forward

- Example



$$z_0^{[1]} = w_{0,0}^{[1]}x_0 + w_{0,1}^{[1]}x_1 + w_{0,2}^{[1]}x_2 + b_0^{[1]}$$
$$a_0^{[1]} = g\left(z_0^{[1]}\right)$$

$$z_1^{[1]} = w_{1,0}^{[1]}x_0 + w_{1,1}^{[1]}x_1 + w_{1,2}^{[1]}x_2 + b_0^{[1]}$$
$$a_1^{[1]} = g\left(z_1^{[1]}\right)$$

$$z_0^{[2]} = w_{0,0}^{[2]}a_0 + w_{0,1}^{[2]}a_1 + b_0^{[2]}$$
$$a_0^{[2]} = g\left(z_0^{[2]}\right)$$

- We have an output, how to change weights and biases to achieve the desired output?
- Error L

Backpropagation

- $$\Delta W = -\alpha \frac{\partial L}{\partial W}$$
- W is a large three dimansional matrix
- Chain rule!

Geoffrey Hinton

FOLLOW

Emeritus Prof. Comp Sci, U.Toronto & Engineering Fellow, Google
Verified email at cs.toronto.edu - Homepage

machine learning neural networks artificial intelligence cognitive science computer science

TITLE	CITED BY	YEAR
Learning internal representations by error-propagation DE Rumelhart, GE Hinton, RJ Williams Parallel Distributed Processing: Explorations in the Microstructure of …	63004 *	1986

Backpropagation

- Chain rule

$$a_i = g(z_i) = g(w_{ij}a_j + b_i)$$

$$\frac{\partial L}{\partial w_{ij}} = \frac{\partial L}{\partial a_i}\frac{\partial a_i}{\partial z_i}\frac{\partial z_i}{\partial w_{ij}} = \frac{\partial L}{\partial a_i}g'(z_i)a_j$$

$$\frac{\partial L}{\partial a_i} = \sum_{l \in L}\frac{\partial L}{\partial a_l}\frac{\partial a_l}{\partial z_l}\frac{\partial z_l}{\partial a_i} = \sum_{l \in L}\frac{\partial L}{\partial a_l}g'(z_l)w_{li}$$

Backpropagation: Example

- From HMKCode
- Note that there is no activation function (it would just add one more step in the chain rule)



Backpropagation: Example

- Weights



Backpropagation: Example

- Feedforward



Backpropagation: Example

- Error from the desired target



$$\text{Error} = \frac{1}{2}(0.191 - 1.0)^2 = 0.327$$

Backpropagation: Example

- Prediction function

$$\textbf{prediction} = \text{out}$$

$$\textbf{prediction} = (h_1)\, w_5 + (h_2)\, w_6$$

$$h_1 = i_1 w_1 + i_2 w_2$$
$$h_2 = i_1 w_3 + i_2 w_4$$

$$\textbf{prediction} = (i_1 \boldsymbol{w_1} + i_2 \boldsymbol{w_2})\, w_5 + (i_1 \boldsymbol{w_3} + i_2 \boldsymbol{w_4})\, w_6$$

to change ***prediction*** value,
we need to change ***weights***

Backpropagation: Example

- Gradient descent

Old weight

Derivative of Error with respect to weight

$$^{*}W_x = W_x - a\left(\frac{\partial Error}{\partial W_x}\right)$$

New weight

Learning rate

$$^{*}W_6 = W_6 - a\left(\frac{\partial Error}{\partial W_6}\right)$$



Backpropagation: Example

- Chain rule

$$\frac{\partial Error}{\partial W_6} = \frac{\partial Error}{\partial prediction} * \frac{\partial prediction}{\partial W_6}$$

chain rule

$$\text{Error} = \frac{1}{2}(\text{prediction} - \text{actual})^2$$

$$\text{prediction} = (i_1 w_1 + i_2 w_2)\, w_5 + (i_1 w_3 + i_2 w_4)\, w_6$$

$$\frac{\partial Error}{\partial W_6} = \frac{\frac{1}{2}(predictoin - actula)^2}{\partial prediciton} * \frac{\partial\, (i_1 w_1 + i_2 w_2)\, w_5 + (i_1 w_3 + i_2 w_4)\, w_6}{\partial W_6}$$

$$\frac{\partial Error}{\partial W_6} = 2 * \frac{1}{2}(\text{predictoin} - \text{actula}) \frac{\partial(predictoin - actula)}{\partial prediciton} * (i_1 w_3 + i_2 w_4)$$

$$h_2 = i_1 w_3 + i_2 w_4$$

$$\frac{\partial Error}{\partial W_6} = (\text{predictoin} - \text{actula}) * (h_2)$$

$$\Delta = \text{prediction} - \text{actual}$$

delta

$$\frac{\partial Error}{\partial W_6} = \Delta h_2$$

Backpropagation: Example

- Chain rule

$$\frac{\partial Error}{\partial W_6} = \frac{\partial Error}{\partial prediction} * \frac{\partial prediction}{\partial W_6}$$

chain rule

Error = $\frac{1}{2}$(prediction – actual)^2

prediction = $(i_1 w_1 + i_2 w_2)\, w_5 + (i_1 w_3 + i_2 w_4)\, w_6$

$$\frac{\partial Error}{\partial W_6} = \frac{\frac{1}{2}(predictoin - actula)^2}{\partial prediciton} * \frac{\partial\,(i_1 w_1 + i_2 w_2)\, w_5 + (i_1 w_3 + i_2 w_4)\, w_6}{\partial W_6}$$

$$\frac{\partial Error}{\partial W_6} = 2 * \frac{1}{2}(\mathbf{predictoin} - \mathbf{actula})\frac{\partial(predictoin - actula)}{\partial prediciton} * (i_1 w_3 + i_2 w_4)$$

$h_2 = i_1 w_3 + i_2 w_4$

$$\frac{\partial Error}{\partial W_6} = (\mathbf{predictoin} - \mathbf{actula}) * (h_2)$$

Δ = prediction – actual

delta

$$\frac{\partial Error}{\partial W_6} = \Delta h_2$$

$$^{*}W_6 = W_6 - a\,\Delta h_2$$

Backpropagation: Example

- Chain rule

$$^{*}W_6 = W_6 - a\,\Delta h_2$$

$$^{*}W_5 = W_5 - a\,\Delta h_1$$



Backpropagation: Example

- Chain rule

$$\frac{\partial Error}{\partial W_1} = \frac{\partial Error}{\partial prediction} * \frac{\partial prediction}{\partial h_1} * \frac{\partial h_1}{\partial W_1}$$

chain rule

Error = $\frac{1}{2}$(prediction – actual)^2

prediction = $(h_1)\, w_5 + (h_2)\, w_6$

$h_1 = i_1 w_1 + i_2 w_2$

$$\frac{\partial Error}{\partial W_1} = \frac{\partial \frac{1}{2}(predictoin - actula)^2}{\partial prediciton} * \frac{\partial\, (h_1)\, w_5 + (h_2)\, w_6}{\partial h_1} * \frac{\partial\, i_1 w_1 + i_2 w_2}{\partial w_1}$$

$$\frac{\partial Error}{\partial W_1} = 2 * \frac{1}{2}(\mathbf{predictoin} - \mathbf{actula}) \frac{\partial (predictoin - actula)}{\partial prediciton} * (w_5) * (i_1)$$

$$\frac{\partial Error}{\partial W_1} = (\mathbf{predictoin} - \mathbf{actula}) * (w_5 i_1)$$

Δ = prediction – actual

delta

$$\frac{\partial Error}{\partial W_1} = \Delta\, w_5 i_1$$



Backpropagation: Example

- Summarized

updated weights

$$
\begin{aligned}
{}^{*}w_6 &= w_6 - a\,(h_2 \,.\, \Delta) \\
{}^{*}w_5 &= w_5 - a\,(h_1 \,.\, \Delta) \\
{}^{*}w_4 &= w_4 - a\,(i_2 \,.\, \Delta w_6) \\
{}^{*}w_3 &= w_3 - a\,(i_1 \,.\, \Delta w_6) \\
{}^{*}w_2 &= w_2 - a\,(i_2 \,.\, \Delta w_5) \\
{}^{*}w_1 &= w_1 - a\,(i_1 \,.\, \Delta w_5)
\end{aligned}
$$

Backpropagation: Example

- Summarized in matrix form

$$\begin{bmatrix} w_5 \\ w_6 \end{bmatrix} = \begin{bmatrix} w_5 \\ w_6 \end{bmatrix} - a\,\Delta \begin{bmatrix} h_1 \\ h_2 \end{bmatrix} = \begin{bmatrix} w_5 \\ w_6 \end{bmatrix} - \begin{bmatrix} a h_1 \Delta \\ a h_2 \Delta \end{bmatrix}$$

$$\begin{bmatrix} w_1 & w_3 \\ w_2 & w_4 \end{bmatrix} = \begin{bmatrix} w_1 & w_3 \\ w_2 & w_4 \end{bmatrix} - a\,\Delta \begin{bmatrix} i_1 \\ i_2 \end{bmatrix} . \begin{bmatrix} w_5 & w_6 \end{bmatrix} = \begin{bmatrix} w_1 & w_3 \\ w_2 & w_4 \end{bmatrix} - \begin{bmatrix} a\, i_1 \Delta w_5 & a\, i_1 \Delta w_6 \\ a\, i_2 \Delta w_5 & a\, i_2 \Delta w_6 \end{bmatrix}$$

How many layers?

- Neural network with at least one hidden layer is a universal approximator (can represent any function).



Do Deep Nets Really Need to be Deep? Jimmy Ba, Rich Caruana,